

SLIM7 Series

Model 736 & 738

COMPACT COUNTERTOP HEAT
TREATMENT SOFT SERVE FREEZERS

LESS DOWNTIME
MORE
THROUGHPUT

Great performance in a smaller
footprint to meet demands of your
busiest dayparts.

FEATURES

- Smaller footprint optimizes valuable space
- Effective heat treatment provides consistent taste and structure
- Gear pump technology easily controls overrun to your given needs
- Heat treatment system provides labor savings
- Recovers quickly for high volume throughput
- Versatility to create a variety of new products



736



738



Smaller Footprint



Heat Treatment System



Gear Pump



Smaller Footprint

The Slim7 Series may be small, but it is mighty, with high volume throughput. A streamlined, compact design and side condenser make it ideal for back counter installation anywhere space is limited.

Heat Treatment System

The Slim7 Series features a daily heating and cooling cycle to help you save on labor costs and reduce product waste. How? It safely maintains dairy products up to two weeks before a complete disassembly and cleaning is required.

Gear Pump

Get the perfect ratio of mix to air every time for improved texture and product consistency, with the gear pump technology used in the Slim7 Series. It features an easily adjustable manual overrun feature, and with less parts, it's easy to assemble and disassemble.

MODEL 736 SPECIFICATIONS AND CAPACITY

Dimensions

Width	15-3/4"	400 mm
Depth	30-7/16"	773 mm
Height	35-3/4"	908 mm

Mounted on standard feet h. 4" (100 mm)

Weight

Net	273.4 lb	124 kg
Crated	339.5 lb	154 kg

Beater Motor One, 2 HP (1500 W)

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	kW
380-415/50/3	15 A	5.5 A	2.6 kW

One dedicated electrical connection is required. Manufactured to be permanently connected. For exact electrical information, always refer to the data label of the unit.

Air cooled.

MODEL 738 SPECIFICATIONS

Dimensions

Width	21-9/64"	537 mm
Depth	31-13/16"	808 mm
Height	38-3/16"	970 mm

Mounted on standard feet h. 4" (100 mm)

Weight

Net	485 lb	220 kg
Crated	573 lb	260 kg

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	kW
380-415/50/3	25	18 A	4.4 kW

One dedicated electrical connection is required. Manufactured to be permanently connected. For exact electrical information, always refer to the data label of the unit.

DISTRIBUTOR INFORMATION



Rockton, IL USA
800.255.0626 | 815.624.8333
www.taylor-company.com
info@taylor-company.com